

RESISTANCES E-96 SERIES 1%

10R0	31R6	97R6	301R	931R	2K80	8K66	26K7	82K5	255K	787K
10R2	32R4	100R	309R	953R	2K87	8K87	27K4	84K5	261K	806K
10R5	33R2	102R	316R	976R	2K94	9K09	28K0	86K6	267K	825K
10R7	34R0	105R	324R	1K00	3K01	9K31	28K7	88K7	274K	845K
11R0	34R8	107R	332R	1K02	3K09	9K53	29K4	90K9	280K	866K
11R3	35R7	110R	340R	1K05	3K16	9K76	30K1	93K1	287K	887K
11R5	36R5	113R	348R	1K07	3K24	10K0	30K9	95K3	294K	909K
11R8	37R4	115R	357R	1K10	3K32	10K2	31K6	97K6	301K	931K
12R1	38R3	118R	365R	1K13	3K40	10K5	32K4	100K	309K	953K
12R4	39R2	121R	374R	1K15	3K48	10K7	33K2	102K	316K	976K
12R7	40R2	124R	383R	1K18	3K57	11K0	34K0	105K	324K	
13R0	41R2	127R	392R	1K21	3K65	11K3	34K8	107K	332K	
13R3	42R2	130R	402R	1K24	3K74	11K5	35K7	110K	340K	
13R7	43R2	133R	412R	1K27	3K83	11K8	36K5	113K	348K	
14R3	44R2	137R	422R	1K30	3K92	12K1	37K4	115K	357K	
14R7	45R3	140R	432R	1K33	4K02	12K4	38K3	118K	365K	
15R0	46R4	143R	442R	1K37	4K12	12K7	39K2	121K	374K	
15R4	47R5	147R	453R	1K40	4K22	13K0	40K2	124K	383K	
15R8	48R7	150R	464R	1K43	4K32	13K3	41K2	127K	392K	
16R2	49R9	154R	475R	1K47	4K42	13K7	42K2	130K	402K	
16R5	51R1	158R	487R	1K50	4K53	14K0	43K2	133K	412K	
16R9	52R3	162R	499R	1K54	4K64	14K3	44K2	137K	422K	
17R4	53R6	165R	511R	1K58	4K75	14K7	45K3	140K	432K	
17R8	54R9	169R	523R	1K62	4K87	15K0	46K4	143K	442K	
18R2	56R2	174R	536R	1K65	4K99	15K4	47K5	147K	453K	
18R7	57R6	178R	549R	1K69	5K11	15K8	48K7	150K	464K	
19R1	59R0	182R	562R	1K74	5K23	16K2	49K9	154K	475K	
19R6	60R4	187R	576R	1K78	5K36	16K5	51K1	158K	487K	
20R0	61R9	191R	590R	1K82	5K49	16K9	52K3	162K	499K	
20R5	63R4	196R	604R	1K87	5K62	17K4	53K6	165K	511K	
21R0	64R9	200R	619R	1K87	5K76	17K8	54K9	169K	523K	
21R5	66R5	205R	634R	1K91	5K90	18K2	56K2	174K	536K	
22R1	68R1	210R	649R	1K96	6K04	18K7	57K6	178K	549K	
22R6	69R8	215R	665R	2K00	6K19	19K1	59K0	182K	562K	
23R2	71R5	221R	681R	2K05	6K34	19K6	60K4	187K	576K	
23R7	73R2	226R	698R	2K10	6K49	20K0	61K9	191K	590K	
24R3	75R0	232R	715R	2K15	6K65	20K5	63K4	196K	604K	
24R9	76R8	237R	732R	2K21	6K81	21K0	64K9	200K	619K	
25R5	78R7	243R	750R	2K26	6K98	21K5	66K5	205K	634K	
26R1	80R6	249R	768R	2K32	7K15	22K1	68K1	210K	649K	
26R7	82R5	255R	787R	2K37	7K32	22K6	69K8	215K	665K	
27R4	84R5	261R	806R	2K43	7K50	23K2	71K5	221K	681K	
28R0	86R6	267R	825R	2K49	7K68	23K7	73K2	226K	698K	
28R7	88R7	274R	845R	2K55	7K87	24K3	75K0	232K	715K	
29R4	90R9	280R	866R	2K61	8K06	24K9	76K8	237K	732K	
30R1	93R1	287R	887R	2K67	8K25	25K5	78K7	243K	750K	
30R9	95R3	294R	909R	2K74	8K45	26K1	80K6	249K	768K	

RESISTANCES E-24 SERIES 5%

1.0R	10R	100R	1K0	10K	100K	1M0				
1.1R	11R	110R	1K1	11K	110K	1M1				
1.2R	12R	120R	1K2	12K	120K	1M2				
1.3R	13R	130R	1K3	13K	130K	1M3				
1.5R	15R	150R	1K5	15K	150K	1M5				
1.6R	16R	160R	1K6	16K	160K	1M6				
1.8R	18R	180R	1K8	18K	180K	1M8				
2.0R	20R	200R	2K0	20K	200K	2M0				
2.2R	22R	220R	2K2	22K	220K	2M2				
2.4R	24R	240R	2K4	24K	240K	2M4				
2.7R	27R	270R	2K7	27K	270K	2M7				
3.0R	30R	300R	3K0	30K	300K	3M0				
3.3R	33R	330R	3K3	33K	330K	3M3				
3.6R	36R	360R	3K6	36K	360K	3M6				
3.9R	39R	390R	3K9	39K	390K	3M9				
4.3R	43R	430R	4K3	43K	430K	4M3				
4.7R	47R	470R	4K7	47K	470K	4M7				
5.1R	51R	510R	5K1	51K	510K	5M1				
5.6R	56R	560R	5K6	56K	560K	5M6				
6.2R	62R	620R	6K2	62K	620K	6M2				
6.8R	68R	680R	6K8	68K	680K	6M8				
7.5R	75R	750R	7K5	75K	750K	7M5				
8.2R	82R	820R	8K2	82K	820K	8M2				
9.1R	91R	910R	9K1	91K	910K	9M1				
低阻質的參考規格 (ohm)				高阻質的參考規格 (ohm)						
0.1	0.01	0.001	0.00075	10M	100M	1G				
0.12	0.012	0.0015	0.0005	12M	120M	1.2G				
0.13	0.013	0.002		15M	150M	1.5G				
0.15	0.015	0.003		16M	160M	1.8G				
0.16	0.016	0.004		18M	180M	2G				
0.18	0.018	0.0045		20M	200M	2.2G				
0.2	0.02	0.005		22M	220M	2.4G				
0.22	0.022	0.006		24M	240M	2.7G				
0.24	0.024	0.0065		27M	270M	3G				
0.27	0.027	0.007		30M	300M	3.3G				
0.3	0.03	0.008		33M	330M	3.6G				
0.33	0.033	0.009		36M	360M	3.9G				
0.36	0.036			39M	390M	4.3G				
0.39	0.039			43M	430M	4.7G				
0.43	0.043			47M	470M	5.1G				
0.47	0.047			51M	510M	5.6G				
0.5	0.05			56M	560M	6.2G				
0.51	0.051			75M	750M	7.5G				
0.62	0.062			82M	820M	8.2G				
0.68	0.068			91M	910M	9.1G				
0.75	0.075					10G				
0.82	0.082									
0.91	0.091									

PS: (1) E96-SERIS (1R~9.9R) or 其他超低值的規格 or 規格表上找不的阻值,都可依您的需求而生產.

(2)E24 SERIES 5% 的規格, 於E96 SERIES 都可生產

(3)此規格表適用於傳統電阻or晶片電阻